

### Vertical Reach: 30.1m



# SYG5210THB 30V8(SZ-AUS) TRUCK-MOUNTED CONCRETE PUMP

#### **Energy-saving**

With cycle times of up to 25 per minute (at 6MPa), pump efficiency is increased up to 25% while fuel consumption is decreased by up to 10%.

#### **Highly Wear Resistant Parts**

The highly wear resistant parts improve efficiency and reduce down time.

#### Safety

Our truck mounted concrete pump exemplifies Sany's precise, rigorous manufacturing philosophy and uncompromising focus on safety.

#### Self-diagnosis Technology

Continually monitors more than 200 aspects of the system during operation. Faults are displayed on the monitor. Review of the detected faults can reduce troubleshooting time by 70%.

## **TECHNICAL SPECIFICATION**

Model			SYG5210THB 30V8(SZ-AUS)
X-unit Specification	Length(mm)		8520
	Width(mm)		2500
	Height(mm)		3350
	Dead weight(kg)		13500
Boom & Outrigger Specification	Vertical reach(m)		30.1
	Horizontal reach(m)		26.5
	Reach depth(m)		15.2
	Unfolded reach(m)		9.6
	1st Section	Length(mm)	7676
		Articulation(°)	89
	2nd Section	Length(mm)	6090
		Articulation(°)	180
	3rd Section	Length(mm)	6100
		Articulation(°)	245
	4th Section	Length(mm)	6635
		Articulation(°)	230
	Rotation(°)		360
	Front outrigger spread L-R(mm)		5850
	Rear outrigger spread L-R(mm)		5420
Pumping Systerm Specification	Output(m³/h)		137
	Pressure(MPa)		6
	Max. strokes per minute(times/min)		34
	Delivery cylinder diameter(mm)		230
	Stroke length(mm)		1600
	Hydraulic system		Open
	Hydraulic system oil pressure(MPa)		32
	Oil tank capacity(L)		320
	Water tank capacity(L)		300
	Pipeline size(mm)		125
	End hose length(m)		3
	End hose diameter(mm)		125
Chassis Specification	Chassis brand		1
	Chassis model		1
	Engine type		1
	Engine maximum net power(kW/rpm)		/
	Emission standard		1
	Capacity of fuel tank (L)		/
	Displacement(L)		1
	Max. speed(km/h)		/





